

TECHNICAL DETAILS

westex.

FLOORING EXCELLENCE

ELYSIAN VELVET COLLECTION



ELYSIAN VELVET COLLECTION



A luxurious velvet carpet range crafted with advanced SilkTex Technology. This innovative material delivers unparalleled sheen and softness while offering superior resistance to pilling and stains, ensuring a long-lasting, elegant finish.

Available in 5 widths:
1.00m, 3.66m (12ft), 4.00m, 4.57m (15ft) & 5.00m

Method of Manufacture:
2 Fold Tufted Cut Pile

Pile Material:
SilkTex

Colour Palette:
15 Standard Colours - Available in both Qualities

2 LUXURY QUALITIES



*+/- 10% commercial tolerance




Westex Carpets Limited.
Calder Bank Mills, Calder Bank Road, Dewsbury WF12 9QW, United Kingdom
Tel: +44 (0)1274 861334 Fax: +44 (0)1274 873266
westexflooring.com info@westexflooring.com

westex.
FLOORING EXCELLENCE

ELYSIAN VELVET COLLECTION


15 COLOUR OPTIONS




Abalone




Travertine



Macademia




Pearl




Ice




Meadow Mist




Kobicha




Canvas




Mink




Soft Pencil



Mossy Stone




Pecan



Porpoise



Seaweed

















Wolf



Westex Carpets Limited.
Calder Bank Mills, Calder Bank Road, Dewsbury WF12 9QW, United Kingdom
Tel: +44 (0)1274 861334 Fax: +44 (0)1274 873266
westexflooring.com info@westexflooring.com

westex.
FLOORING EXCELLENCE

Technical Specification

Luxury Rating	BS EN 1307:2014	LC5	
End Use Classification	BS EN 1307:2014	Class 23 Heavy Domestic Use Class 33 Heavy Commercial Use	 
Hexapod 4000	BS EN 1307:2014	4.5	
Hexapod 12000	BS EN 1307:2014	4.0	
Roll Widths*		Available in 5 sizes: • 1.00m • 3.66m (12ft) • 4.00m • 4.57m (15ft) • 5.00m	
Roll Length		Customisable	
Method of Manufacture		2 Fold Tufted Cut Pile	
Tuft Density*	ISO 1763	216,535 per m ²	
Pile Material		SilkText	
Pile Height above Backing*		12.5mm	
Total Carpet Thickness*		14.0mm	
Primary Backing		Polypropylene	
Flammability	BS4790 Hot Nut Test	Low Radius of Char	
Reaction to Fire	BS EN 13501	Class E _{fl}	
Delamination	BS ISO 11857	Pass Minimum 15.00 (N)	
Thermal resistance	BS4745	1.26 tog	
Dimensional Stability	ISO 2551-1981 (2010)	Pass Pass if shrinkage is equal to or less than 1.2% and extension less than or equal to 0.5%	
Colour Fastness: Light Colour Fastness: Shampooing Colour Fastness: Rubbing	BS EN ISO -B02 BS ISO -18168 BS EN ISO -X12	6+ 5 5	
Electrical Resistance	ISO 10965:2011	Pass Does not exceed 10Ω	
Sound Absorption		Class E (H) with Underlay	
Underfloor heating system		Suitable to a max. 27°C Please check with manufacturers guidelines	
Warranty		6 Years	
CE Mark	EN 14041		














*Commercial Tolerance +/- 10%



Westex Carpets Limited.
Calder Bank Mills, Calder Bank Road, Dewsbury WF12 9QW, United Kingdom
Tel: +44 (0)1274 861334 Fax: +44 (0)1274 873266
westexflooring.com info@westexflooring.com



Technical Specification

Luxury Rating	BS EN 1307:2014	LC5	
End Use Classification	BS EN 1307:2014	Class 23 Heavy Domestic Use Class 33 Heavy Commercial Use	
Hexapod 4000	BS EN 1307:2014	4.5	
Hexapod 12000	BS EN 1307:2014	4.0	
Roll Widths*		Available in 5 sizes: • 1.00m • 3.66m (12ft) • 4.00m • 4.57m (15ft) • 5.00m	
Roll Length		Customisable	
Method of Manufacture		2 Fold Tufted Cut Pile	
Tuft Density*	ISO 1763	196,850 per m ²	
Pile Material		SilkText	
Pile Height above Backing*		9.5mm	
Total Carpet Thickness*		11.0mm	
Primary Backing		Polypropylene	
Flammability	BS4790 Hot Nut Test	Low Radius of Char	
Reaction to Fire	BS EN 13501	Class E _{fl}	
Delamination	BS ISO 11857	Pass Minimum 15.00 (N)	
Thermal resistance	BS4745	1.12 tog	
Dimensional Stability	ISO 2551-1981 (2010)	Pass Pass if shrinkage is equal to or less than 1.2% and extension less than or equal to 0.5%	
Colour Fastness: Light Colour Fastness: Shampooing Colour Fastness: Rubbing	BS EN ISO -B02 BS ISO -18168 BS EN ISO -X12	6+ 5 5	
Electrical Resistance	ISO 10965:2011	Pass Does not exceed 10Ω	
Sound Absorption		Class E (H) with Underlay	
Underfloor heating system		Suitable to a max. 27°C Please check with manufacturers guidelines	
Warranty		6 Years	
CE Mark	EN 14041		

*Commercial Tolerance +/- 10%



Westex Carpets Limited.
Calder Bank Mills, Calder Bank Road, Dewsbury WF12 9QW, United Kingdom
Tel: +44 (0)1274 861334 Fax: +44 (0)1274 873266
westexflooring.com info@westexflooring.com





*A minimum order quantity of 40m² in any one width applies.



Westex Carpets Limited.
Calder Bank Mills, Calder Bank Road, Dewsbury WF12 9QW, United Kingdom
Tel: +44 (0)1274 861334 Fax: +44 (0)1274 873266
westexflooring.com info@westexflooring.com

westex.
FLOORING EXCELLENCE